

Product Information				
<b>Product Description:</b>	<b>7.0" USB monitor</b>			
<b>Model Name:</b>	MIMO UM-760			
<b>Model Type:</b>	Slider			
Product picture		Product Specifications		
		<b>Product Features</b>		
		<ul style="list-style-type: none"> <li>- High Speed USB2.0 Powered / Interfaced (USB Plug &amp; Play)</li> <li>- No touchscreen</li> <li>- Brighth, Vibrant, High-resolution LCD Display</li> <li>- High Gloss Black Finish, Stylish Design</li> <li>- Swivel the monitor anytime to suit your application</li> <li>- Instant Extention / Mirror Display Mode Support</li> <li>- Low-Energy Efficient Mini-Display to set up various applications; Program Icons, E-Mail Checking, Incoming Phone Numbers, Car-pc monitor, Screen of Point of sale for Customers, Secondary Screen for use in industrial monitoring ... etc.</li> </ul>		
		<b>Technical Data</b>		
 <b>LC Design</b> Ihr Partner für LCD-Module, Testgeräte, Controllerplatinen, Adapter, Entwicklung und Support  <a href="https://www.lcdstore.de/MIMO-Monitore/7-Zoll">https://www.lcdstore.de/MIMO-Monitore/7-Zoll</a>		Display	Screen Size	7.0"
			Resolution	WSVGA (1024x600)
			Brightness	250 cd/m <sup>2</sup>
			Contrast Ratio	700:1
		Signal Input	Response Time	10 msec
			Touch Input	No touchscreen
			Video Input	USB2.0 High Speed
		Power	Connector	USB Mini B Type
			Power Input	USB Power (5V, current depending on brightness setting, 400mA-900mA) *
			Power Consumption	2.0 ~ 4.5W*
Feature	UI, Pivot	Pivot (Landscape, Portrait)		
PC Requirement	Processor	Intel Pentium/Celeron/AMD/K6/ Athlon/Duron 1.2GHz or above		
	RAM	512MB or above		
	HDD	30MB HDD space above		
	OS	Windows Xp/7/8/10 Mac supported		
	Size	185(W) x 145(H) x 24(D) mm		
	Weight	330g		

\* A USB 2.0 interface of a PC, laptop or tablet, is specified to allow a current of 500 mA to supply a device connected to that USB-connection. PCs typically supply a higher current, so a MIMO normally can work on one USB connection of a PC. Laptops and especially tablets are designed for low power consumption, so the current specification of the USB interface typically is not outperformed, but in many cases not met.

It that case we recommend to use an Y-cable to connect two USB interfaces. Two adjacent connectors are the best choice to reduce compensating currents between the two USB connections.

A power supply with an USB connector linked to the Y-cable is the second best choice to achieve the necessary supply current. Due to a possible higher voltage difference between the USB connector of the host and the power supply compensating currents are more likely, which probably can damage the USB interface of the host.

The USB-A connector of the included USB cable also fits a USB-A connector of USB 3.0 (blue connector core). USB 3.0 is specified to supply 900mA.