

Product Information					
<b>Product Description:</b>	<b>10.1" USB monitor</b>				
<b>Model Name:</b>	MIMO UM-1080-OF				
<b>Model Type:</b>	open frame				
Product picture		Product Specifications			
   <p style="text-align: right;"></p>		Product Features			
		<ul style="list-style-type: none"> <li>- High Speed USB2.0 Powered / Interfaced (USB Plug &amp; Play)</li> <li>- no Touchscreen Panel</li> <li>- Bright, Vibrant, High-resolution LCD Display</li> <li>- High Gloss Black Finish, Stylish Design</li> <li>- Swivel the monitor anytime to suit your application</li> <li>- Instant Extension / Mirror Display Mode Support</li> <li>- Low-Energy Efficient Mini-Display to set up various applications; Program Icons, E-Mail Checking, Incoming Phone Numbers, Car-pc monitor, Screen of Point of sale for Customers, Secondary Screen for use in industrial monitoring ... etc.</li> </ul>			
 <p><b>LC Design</b> Ihr Partner für LCD-Module, Testgeräte, Controllerplatinen, Adapter, Entwicklung und Support</p> <p><a href="https://www.lcdstore.de/MIMO-Monitore/10-Zoll">https://www.lcdstore.de/MIMO-Monitore/10-Zoll</a></p>		Technical Data			
		Display	Screen Size	10.1" AA 215,96 (H) x 135,60 (W) mm	
			Resolution	WXGA (1280x800) IPS	
			Brightness	350 cd/m <sup>2</sup>	
			Contrast Ratio	800:1	
			Response Time	15 msec	
		Signal Input	Touch Input	no Touch Panel	
Video Input	USB2.0 High Speed				
Connector	USB Mini B Type				
Power	Power Input	USB Power (5V, current depending on brightness setting, 500mA-1000mA) *			
	Power Consumption	2.0 ~ 4.5W*			
Feature	Pivot	Landscape, Portrait			
PC Requirement	Processor	Intel Pentium/Celeron/AMD/K6/ Athlon/Duron 1.2GHz or above			
	RAM	1GB or above			
	HDD	30MB HDD space above			
	OS	Windows Xp/7/8/10 Mac supported			
Size		248,0(W) x 151,7(H) x 14,2(D) mm			
Weight		410g			

\* A USB 2.0 interface of a PC, laptop or tablet, is specified to allow a current of 500 mA to supply a device connected to that USB-connection. PCs typically supply a higher current, so a MIMO normally can work on one USB connection of a PC. Laptops and especially tablets are designed for low power consumption, so the current specification of the USB interface typically is not outperformed, but in many cases not met.

It that case we recommend to use an Y-cable to connect two USB interfaces. Two adjacent connectors are the best choice to reduce compensating currents between the two USB connections.

A power supply with an USB connector linked to the Y-cable is the second best choice to achieve the necessary supply current. Due to a possible higher voltage difference between the USB connector of the host and the power supply compensating currents are more likely, which probably can damage the USB interface of the host.

The USB-A connector of the included USB cable also fits a USB-A connector of USB 3.0 (blue connector core). USB 3.0 is specified to supply 900mA.